

# Intra chroma prediction using inter-channel correlation


**JCTVC-B021**

**J.Kim, S.Park, Y.Choi, Y.Jeon, B.Jeon**



# Introduction

- Propose a new ‘intra chroma prediction’
- Basic idea
  - Prediction of chroma from luma



- Using the correlation between chroma and luma

$$C[x, y] = \alpha \times L[x, y] + \beta$$


- Apply the idea to ‘intra chroma prediction’

# Proposed method

- Use the reconstructed luma samples with same sampling position with chroma samples

$$pred_C[x, y]$$

$$= \alpha \times \{ (P_L[2x, 2y] + P_L[2x, 2y+1]) \gg 1 \} + \beta$$




# Proposed method

- **Derivation of parameters  $\alpha$  and  $\beta$** 
  - Least-squares method
  - Neighboring samples around current block are used

$$\alpha = \frac{R(\hat{P}_L, P'_C)}{R(\hat{P}_L, \hat{P}_L)}, \quad \beta = M(P'_C) - \alpha \times M(\hat{P}_L)$$

$M(A)$  : Mean of  $A$        $R(A, B) = M((A - M(A)) \times (B - M(B)))$




# Proposed method

## ■ Summary

Prediction of chroma block

=  $\alpha \times$  **Reconstructed luma samples with same sampling position with chroma samples** +  $\beta$

, where  $\alpha$  and  $\beta$  are derived by least-squares method using **the neighboring pixels around target block**



# Proposed method

- **Signaling of the proposed method**
  - 1bit flag (intra\_chroma\_estimation\_flag)
    - 1 : Proposed method
    - 0 : Conventional method (e.g. H.264 intra chroma pred.)
- **Proposed method is applied to both U and V comp. in the same way**

# Test conditions

- **Test conditions are based on JCTVC-B004 (Intra prediction AHG)**
  - Implemented on JM-KTA 2.6r1
  - Two QP sets
    - {22, 26, 30, 34} – Lower QPs
    - {26, 30, 34, 38} – Higher QPs
  - Coding configurations
    - Intro only coding
    - CS1 – GOP8
  - For Class A seq., bit-depth is set to 8 instead of 12 due to memory limitation
  - For CS1, Class A sequences are not tested due to lack of time
  - Comparison
    - **Anchor** (JM-KTA 2.6r1)
    - **Proposed** (JM-KTA 2.6r1 + proposed method)

# Objective quality results

- **BD Rate(%) for all sequences**

Intra only coding		Lower QP set			Higher QP set		
		Y	U	V	Y	U	V
	Avg.	-1.59	-5.11	-4.09	-1.56	-7.42	-5.72
Max.	-7.24	-11.44	-12.55	-8.08	-18.54	-18.83	

CS1		Lower QP set			Higher QP set		
		Y	U	V	Y	U	V
	Avg.	-0.88	-5.25	-4.26	-0.97	-7.27	-5.88
Max.	-3.05	-9.57	-8.52	-3.80	-13.88	-11.65	

# Objective quality results


- **More than 55% chroma blocks** are coded with the proposed method on average for all QPs of all sequences under intra only constraint
- For Basketball drill sequence, **73% chroma blocks** are coded with the proposed method on average for all QPs under intra only constraint

## Subjective quality comparison

- **U component** (Frame#14 of Basketball Drill / QP36)



**JM-KTA 2.6r1**



**JM-KTA 2.6r1 + Proposed**

## Subjective quality comparison

- **V component** (Frame#14 of Basketball Drill / QP36)



JM-KTA 2.6r1



JM-KTA 2.6r1 + Proposed

# Conclusion

- **New intra chroma prediction using luma comp.**
- **Improvements in objective(BD-Rate) and subjective qualities**
  - **Significant improvement for chroma**
    - Intra only coding, higher QP set {26, 30, 34, 38}
      - On average, **-7.4%** for U comp. **-5.7%** for V comp.
      - Maximum, **-18.5%** for U comp., **-18.8%** for V comp.
  - **Reasonable improvement for luma**
    - Intra only coding, higher QP set {26, 30, 34, 38}
      - On average, **-1.6%**
      - Maximum, **-8.1%**
- **More efficient for 4:2:2 or 4:4:4 coding**
- **Recommend the proposed scheme to be studied within TE**