

# Decoder-side Block Boundary Decision (DBBD) with OBMC


**JCTVC-C137**

Shigeru Fukushima  
JVC KENWOOD Holdings, Inc. (JVC)

# 1. Outline

- Proposed technique
  - **DBBD** (Decoder-side Block Boundary Decision) **with OBMC**
  - DBBD was proposed in the JCTVC-A108
- About DBBD
  - Inter prediction technique
  - Exploit the correlation **between actual motion boundary** and **object boundary**
- Implementation
  - **JM16.2** base
  - Same syntax as AVC perfectly
  - Implemented only to 16x8 and 8x16 mode
- BD-rate
  - Average gain **3.1%** for **Random Access**
  - Average gain **2.2%** for **Low Delay**

## 2. DBBD Algorithm





## ■ Conventional techniques


- **mismatch** between the block boundary and actual motion boundary
- the **additional coding bits** required

Desired block division

AVC block division




 Prediction error




Fixed block patterns in AVC

It is desirable to support **various block patterns without additional coding bits** for MC.


MC with **various block patterns** without additional coding bits  
- the block boundary is decided **on the decoder-side**






## ■ Decoding procedure

1. Generate two prediction blocks based on two MVs by the size of macroblock.
2. Evaluate each candidate boundary in order to decide the boundary.
3. Perform OBMC along the decided boundary using two prediction blocks.
4. Obtain the final MC block by replacing the pixels around the boundary with OBMC filtered samples.




## ■ Decoding procedure

1. Generate two prediction blocks based on two MVs by the size of macroblock.
2. Evaluate each candidate boundary in order to decide the boundary.
3. Perform OBMC along the decided boundary using two prediction blocks.
4. Obtain the final MC block by replacing the pixels around the boundary with OBMC filtered samples.



## ■ Decoding procedure

1. Generate two prediction blocks based on two MVs by the size of macroblock.
2. Evaluate each candidate boundary in order to decide the boundary.
3. Perform OBMC along the decided boundary using two prediction blocks.
4. Obtain the final MC block by replacing the pixels around the boundary with OBMC filtered samples.




## ■ Decoding procedure

1. Generate two prediction blocks based on two MVs by the size of macroblock.
2. Evaluate each candidate boundary in order to decide the boundary.
3. Perform OBMC along the decided boundary using two prediction blocks.
4. Obtain the final MC block by replacing the pixels around the boundary with OBMC filtered samples.


# Boundary Evaluation

## How to evaluate the boundary?

- calculate three **Activities** across the candidate boundary
- measure **NEV (Neighboring Efficiency Value)**



(d) NEV (Neighboring Efficiency Value)



## Boundary evaluation elements

- (a) on prediction block 1 by **MV1**
- (b) on prediction block 2 by **MV2**
- (c) on connected two prediction blocks by **MV1** and **MV2**
- (d) compare **extended prediction blocks** with reconstructed pixels in neighboring region

Element	Activity1	Activity2	Activity3	NEV
Better value	Larger	Larger	Smaller	Smaller

## When?



- after decision of the boundary

## Why?

- improve the quality of MC block

## How?

- overlap two MC blocks along the boundary



- Software
  - JM16.2
- Syntax
  - Same as AVC perfectly
- Prediction Mode
  - Applied only to 16x8 and 8x16 mode as 16xN and Nx16, respectively
- PMV
  - Same as AVC
- Transform Size
  - Same as AVC (only 8x8 or 4x4 used)
- Others
  - The candidate boundary is restricted to 4, 6, 8, 10, and 12
  - Only luma prediction samples are used to evaluate the boundary

# 3

## 3. Simulation Results

## Match with HEVC common test conditions as much as possible

- Test Sequences
  - All common test sequences are used
  - All frames are encoded
- Coding Structure
  - **Random Access** and **Low Delay**
  - **I/P/B frame** for Random Access
  - **I/B frame** for Low Delay
- Reference Frames
  - **Two** reference frames on **P-frame**
  - **One** reference frame for **each list on B-frame**
- Quantization parameter
  - 22, 27, 32, and 37 for I-frame

# BD-rate Results

- Average gain **3.1%** and up to 4.9% for **Random Access**
- Average gain **2.2%** and up to 3.3% for **Low Delay**

Class	Test Sequence	Random Access	Low Delay
Class A	Traffic	-2.8	-
	PeopleOnStreet	-4.9	-
Class B	Kimono	-1.8	-1.0
	ParkScene	-2.3	-1.6
	Cactus	-2.6	-2.3
	BasketballDrive	-3.0	-2.3
	BQTerrace	-3.2	-2.0
Class C	BasketballDrill	-3.2	-2.8
	BQMall	-3.7	-3.0
	PartyScene	-2.2	-1.4
	RaceHorses	-4.3	-3.0
Class D	BasketballPass	-3.0	-2.3
	BQSquare	-2.6	-1.9
	BlowingBubbles	-2.2	-1.9
	RaceHorses	-4.3	-3.0
Class E	Vidyo1	-	-1.8
	Vidyo3	-	-3.3
	Vidyo4	-	-1.9
<b>Average</b>		<b>-3.1</b>	<b>-2.2</b>

# 4. Conclusion

- Proposed technique
  - **DBBD** (Decoder-side Block Boundary Decision) **with OBMC**
- Software
  - JM16.2 base
- BD-rate
  - Average gain **3.1%** for **Random Access**
  - Average gain **2.2%** for **Low Delay**
- Future Work
  - Confirm the effectiveness of DBBD on TMuC/TM software
  - Participate in TE/CE as a proponent

# JVC KENWOOD HOLDINGS

