

# Modified MVD coding for CABAC

*Hisao Sasai*

*Takahiro Nishi*

**Panasonic Corporation**

**Panasonic** ideas for life


## Motivation

- ✓ To reduce a line buffer for MVD context selection (same as F429)
- ✓ To increase parallel processing capability


## Current design of HEVC

- ✓ 1 bit per PU has to be stored for context selection for MVD  
( All of parameters which use neighbouring data are considered in JCTVC-F429 )
  - ✓ The bypass processing can be done by parallel within bypass coding part. (It is considered in JCTVC-F130 by TI)
- Those complexity reduction could be done by  
Simple modification of MVD coding


## Proposed Solution



### Current HM/WD



### Proposal



## Proposed solution

Single Context is used for bin0 (no depends on neighbours)

## Simulation Results

### Proposal vs HMv3.0 (cross-checked by TI)

	Random Access HE			Low delay B HE		
	Y	U	V	Y	U	V
<b>Overall</b>	<b>-0.02</b>	<b>-0.02</b>	<b>-0.08</b>	<b>-0.02</b>	<b>0.00</b>	<b>0.08</b>
Enc Time[%]	99%			99%		
Dec Time[%]	100%			100%		

(additional information)

### Proposal vs HMv3.0+SingleMVD bin0 (JCTVC-F429)

	Random Access HE			Low delay B HE		
	Y	U	V	Y	U	V
<b>Overall</b>	<b>0.00</b>	<b>0.00</b>	<b>0.00</b>	<b>0.00</b>	<b>0.00</b>	<b>0.00</b>
Enc Time[%]	100%			99%		
Dec Time[%]	98%			98%		

By our proposal,  
reduction of necessity of the line buffer of MVD  
increasing the possibility for parallel processing for MVDcoding  
are realized without any performance drop.  
Text and Code are available.

For single context for MVD bin0  
same solution is proposed in  
JCTVC-F133,F429,F497,F606

For concatenation of bypass coding  
similar solution is proposed in  
JCTVC-F130 for transform coefficient coding

## Recommendation

To be adopted this proposal in HM/WD.

## # Motivation

- To reduce a line buffer for MVD context selection
- To increase parallel processing capability

## #Solution

- single context is used for 1<sup>st</sup> bin of MVD  
( same solution is proposed in F133,F429,F497,F606 )
- concatenate suffix part (bypass) of each components (x,y).

## #Results

- no loss (0.02% gain) all configuration  
with reduction of necessity of line buffer and increasing of possibility for PCP

## #Cross-Checked by TI