

Reference Pictures for Low Delay Settings

Chong Soon Lim
Sue Mon Thet Naing
Viktor Wahadaniah

Panasonic Corporation


Reference Pictures Used in HM-3.0

HM-3.0

- Using 4 reference pictures
- Selecting the nearest reference pictures for both List0 and List1.

Reference Pictures used in HM-3

| | | |
|--------|----------------|----------------|
| POC 0 | [L0] | [L1] |
| POC 1 | [L0 0] | [L1 0] |
| POC 2 | [L0 1 0] | [L1 1 0] |
| POC 3 | [L0 2 1 0] | [L1 2 1 0] |
| POC 4 | [L0 3 2 1 0] | [L1 3 2 1 0] |
| POC 5 | [L0 4 3 2 1] | [L1 4 3 2 1] |
| POC 6 | [L0 5 4 3 2] | [L1 5 4 3 2] |
| POC 7 | [L0 6 5 4 3] | [L1 6 5 4 3] |
| POC 8 | [L0 7 6 5 4] | [L1 7 6 5 4] |
| POC 9 | [L0 8 7 6 5] | [L1 8 7 6 5] |
| POC 10 | [L0 9 8 7 6] | [L1 9 8 7 6] |
| POC 11 | [L0 10 9 8 7] | [L1 10 9 8 7] |
| POC 12 | [L0 11 10 9 8] | [L1 11 10 9 8] |




Reference Pictures Used in JCTVC-F433

JCTVC-F433

- Using 4 reference pictures
- Selecting only the two nearest reference pictures and two of the high quality reference pictures.

Reference Pictures used in proposal

| | | |
|--------|----------------|----------------|
| POC 0 | [L0] | [L1] |
| POC 1 | [L0 0] | [L1 0] |
| POC 2 | [L0 1 0] | [L1 1 0] |
| POC 3 | [L0 2 1 0] | [L1 2 1 0] |
| POC 4 | [L0 3 2 1 0] | [L1 3 2 1 0] |
| POC 5 | [L0 4 3 2 0] | [L1 4 3 2 0] |
| POC 6 | [L0 5 4 3 0] | [L1 5 4 3 0] |
| POC 7 | [L0 6 5 4 0] | [L1 6 5 4 0] |
| POC 8 | [L0 7 6 4 0] | [L1 7 6 4 0] |
| POC 9 | [L0 8 7 4 0] | [L1 8 7 4 0] |
| POC 10 | [L0 9 8 4 0] | [L1 9 8 4 0] |
| POC 11 | [L0 10 9 8 4] | [L1 10 9 8 4] |
| POC 12 | [L0 11 10 8 4] | [L1 11 10 8 4] |




Reference Pictures Memory Management

JCTVC-F433

4 reference pictures


- Key frames are kept slightly longer than the non-key reference frames in reference frame buffer.
- When all buffers are full and another key frame enters the key frame buffer, the oldest key frame is removed from the reference frame buffer.
- Otherwise, the oldest non-key frame is removed from the reference frame buffer based on the sliding window operation.



Reference Pictures Memory Management

JCTVC-F433

2 reference pictures



Reference pictures memory management scheme for JCTVC-F433, using 2 reference pictures

Experimental Results

Experimental results for low delay settings
using 4 reference pictures

Experimental Results

4 reference pictures

| IBBB | Low delay B | | | Low delay LoCo B | | |
|-------------|-------------|-----------|-----------|------------------|-----------|-----------|
| | Y BD-rate | U BD-rate | V BD-rate | Y BD-rate | U BD-rate | V BD-rate |
| Class A | | | | | | |
| Class B | -1.8 | -2.7 | -2.8 | -2.1 | -3.5 | -4.3 |
| Class C | -3.1 | -3.1 | -3.5 | -3.3 | -3.9 | -4.1 |
| Class D | -3.3 | -3.4 | -3.9 | -3.7 | -5.4 | -5.7 |
| Class E | -0.7 | -0.9 | -1.7 | -1.0 | -0.9 | -1.7 |
| All | -2.3 | -2.6 | -3.0 | -2.6 | -3.6 | -4.1 |
| Enc Time[%] | 104.5% | | | 106.4% | | |
| Dec Time[%] | 97.0% | | | 97.0% | | |

Average BD-rate (%) for low delay B settings

| IPPP | Low delay P | | | Low delay LoCo P | | |
|-------------|-------------|-----------|-----------|------------------|-----------|-----------|
| | Y BD-rate | U BD-rate | V BD-rate | Y BD-rate | U BD-rate | V BD-rate |
| Class A | | | | | | |
| Class B | -1.7 | -2.7 | -2.8 | -1.7 | -3.1 | -3.4 |
| Class C | -2.9 | -2.9 | -3.3 | -3.0 | -3.6 | -3.5 |
| Class D | -3.4 | -3.4 | -3.8 | -3.7 | -4.8 | -5.1 |
| Class E | -0.7 | -0.8 | -1.0 | -0.7 | -0.4 | -0.9 |
| All | -2.2 | -2.6 | -2.9 | -2.3 | -3.1 | -3.4 |
| Enc Time[%] | 105.8% | | | 108.6% | | |
| Dec Time[%] | 96.7% | | | 96.7% | | |

Average BD-rate (%) for low delay P settings

Experimental Results

4 reference pictures

- Anchor : HM-3.0 default configuration (NumOfReference = 4)
- Results for JCTVC-F433 using 4 references pictures

| Class | Sequence | BD-rate - Low delay B | | | BD-rate - Low delay B (Loco) | | | BD-rate - Low delay P | | | BD-rate - Low delay P (Loco) | | |
|---------|---------------------|-----------------------|------|------|------------------------------|-------|-------|-----------------------|------|------|------------------------------|-------|-------|
| | | Y | U | V | Y | U | V | Y | U | V | Y | U | V |
| Class B | S03 Kimono | -0.3 | -0.2 | -0.5 | -0.3 | -0.8 | -0.6 | -0.2 | -0.5 | -0.3 | -0.2 | -0.6 | -0.4 |
| | S04 ParkScene | -1.8 | -2.3 | -2.2 | -1.9 | -3.2 | -4.0 | -1.5 | -2.0 | -2.1 | -1.6 | -2.5 | -3.3 |
| | S05 Cactus | -3.4 | -3.8 | -4.4 | -3.5 | -2.9 | -3.7 | -3.2 | -4.1 | -4.0 | -3.1 | -2.6 | -3.1 |
| | S06 BasketballDrive | -0.5 | -1.4 | -0.9 | -0.6 | -1.3 | -1.0 | -0.4 | -1.0 | -0.5 | -0.4 | -1.3 | -0.8 |
| | S07 BQTerrace | -3.2 | -6.0 | -6.1 | -4.4 | -9.4 | -12.2 | -3.2 | -5.8 | -7.0 | -3.5 | -8.4 | -9.2 |
| Class C | S08 BasketballDrill | -5.2 | -4.7 | -6.0 | -5.4 | -4.7 | -5.0 | -4.7 | -4.0 | -5.7 | -4.8 | -5.2 | -4.7 |
| | S09 BQMall | -0.9 | -1.0 | -1.1 | -1.2 | -2.4 | -2.4 | -0.9 | -1.1 | -1.2 | -1.0 | -2.2 | -1.6 |
| | S10 PartyScene | -4.8 | -4.8 | -4.7 | -5.2 | -5.9 | -6.6 | -4.6 | -4.8 | -4.6 | -5.0 | -5.4 | -6.0 |
| | S11 RaceHorsesC | -1.5 | -1.9 | -2.1 | -1.6 | -2.5 | -2.3 | -1.3 | -1.7 | -1.8 | -1.1 | -1.6 | -1.8 |
| Class D | S12 BasketballPass | -1.1 | -2.0 | -1.5 | -1.1 | -1.3 | -1.0 | -1.1 | -1.4 | -1.2 | -1.1 | -1.4 | -1.0 |
| | S13 BQSquare | -7.3 | -6.0 | -7.9 | -8.8 | -13.7 | -14.7 | -8.2 | -7.7 | -9.5 | -9.1 | -12.7 | -13.4 |
| | S14 BlowingBubbles | -3.7 | -3.9 | -4.6 | -3.7 | -4.7 | -5.2 | -3.4 | -3.4 | -3.5 | -3.4 | -4.3 | -4.4 |
| | S15 RaceHorsesD | -1.1 | -1.6 | -1.6 | -1.3 | -1.7 | -1.8 | -1.0 | -0.9 | -1.3 | -1.0 | -1.0 | -1.8 |
| Class E | S16 Vidyo1 | -0.7 | -0.7 | -1.1 | -0.8 | -1.2 | -1.6 | -0.3 | -0.4 | -0.4 | -0.6 | -0.5 | -0.7 |
| | S17 Vidyo3 | 0.0 | -0.1 | -1.8 | -0.5 | -0.3 | -0.8 | -0.4 | -0.6 | -0.1 | -0.1 | 0.5 | -0.5 |
| | S18 Vidyo4 | -1.4 | -1.9 | -2.3 | -1.6 | -1.3 | -2.7 | -1.5 | -1.4 | -2.6 | -1.3 | -1.1 | -1.4 |

Per sequence BD-rate (%) for all low delay settings

Experimental Results

Experimental results for low delay settings
using 2 reference pictures

Experimental Results

2 reference pictures

| IBBB | Low delay B | | | Low delay LoCo B | | |
|-------------|-------------|-----------|-----------|------------------|-----------|-----------|
| | Y BD-rate | U BD-rate | V BD-rate | Y BD-rate | U BD-rate | V BD-rate |
| Class A | | | | | | |
| Class B | -1.8 | -2.8 | -3.0 | -2.2 | -4.8 | -6.1 |
| Class C | -3.5 | -3.7 | -3.9 | -4.3 | -6.2 | -6.5 |
| Class D | -5.3 | -6.2 | -7.4 | -6.3 | -9.7 | -10.9 |
| Class E | -3.9 | -3.8 | -3.4 | -3.2 | -3.6 | -2.7 |
| All | -3.5 | -4.1 | -4.4 | -3.9 | -6.2 | -6.8 |
| Enc Time[%] | 100.0% | | | 100.8% | | |
| Dec Time[%] | 97.8% | | | 98.1% | | |

Average BD-rate (%) for low delay B settings

| IPPP | Low delay P | | | Low delay LoCo P | | |
|-------------|-------------|-----------|-----------|------------------|-----------|-----------|
| | Y BD-rate | U BD-rate | V BD-rate | Y BD-rate | U BD-rate | V BD-rate |
| Class A | | | | | | |
| Class B | -2.2 | -3.3 | -3.2 | -2.1 | -4.0 | -4.8 |
| Class C | -3.4 | -3.5 | -3.7 | -3.8 | -5.2 | -5.7 |
| Class D | -5.0 | -5.8 | -7.3 | -5.5 | -8.9 | -10.0 |
| Class E | -4.1 | -2.8 | -3.4 | -3.5 | -2.3 | -2.3 |
| All | -3.5 | -3.9 | -4.4 | -3.6 | -5.2 | -5.9 |
| Enc Time[%] | 101.7% | | | 101.4% | | |
| Dec Time[%] | 97.5% | | | 97.9% | | |

Average BD-rate (%) for low delay P settings

Experimental Results

2 reference pictures

- Anchor : HM-3.0 default configuration with “NumOfReference = 2”
- Results for JCTVC-F433 using 2 references pictures

| Class | Sequence | BD-rate - Low delay B | | | BD-rate - Low delay B (Loco) | | | BD-rate - Low delay P | | | BD-rate - Low delay P (Loco) | | |
|---------|---------------------|-----------------------|-------|-------|------------------------------|-------|-------|-----------------------|-------|-------|------------------------------|-------|-------|
| | | Y | U | V | Y | U | V | Y | U | V | Y | U | V |
| Class B | S03 Kimono | -0.6 | -0.6 | -0.6 | -0.8 | -2.2 | -2.3 | -0.6 | -1.1 | -0.7 | -0.7 | -1.5 | -1.9 |
| | S04 ParkScene | -2.4 | -2.6 | -2.2 | -2.5 | -4.3 | -5.1 | -2.3 | -2.2 | -2.6 | -2.4 | -4.0 | -4.2 |
| | S05 Cactus | -2.6 | -1.8 | -3.1 | -2.2 | -0.7 | -3.3 | -3.2 | -2.4 | -2.9 | -2.5 | -0.6 | -2.9 |
| | S06 BasketballDrive | -1.0 | -1.8 | -1.3 | -1.4 | -3.2 | -2.8 | -1.1 | -2.2 | -1.6 | -1.1 | -2.2 | -2.3 |
| | S07 BQTerrace | -2.3 | -7.4 | -8.0 | -4.4 | -13.7 | -17.2 | -3.6 | -8.7 | -8.3 | -3.7 | -11.5 | -12.8 |
| Class C | S08 BasketballDrill | -3.0 | -3.0 | -3.1 | -3.6 | -3.7 | -4.2 | -3.1 | -2.8 | -3.2 | -3.1 | -3.6 | -4.1 |
| | S09 BQMall | -1.6 | -1.6 | -1.8 | -2.3 | -5.7 | -5.0 | -1.6 | -1.8 | -1.5 | -1.9 | -3.4 | -3.8 |
| | S10 PartyScene | -8.3 | -8.2 | -8.5 | -10.0 | -13.6 | -14.7 | -7.5 | -7.5 | -8.0 | -9.0 | -12.0 | -13.1 |
| | S11 RaceHorsesC | -1.1 | -1.9 | -2.3 | -1.2 | -2.0 | -1.9 | -1.5 | -1.9 | -2.1 | -1.2 | -1.7 | -1.8 |
| Class D | S12 BasketballPass | -1.1 | -1.1 | -1.0 | -1.2 | -1.1 | -1.3 | -1.0 | -1.1 | -0.8 | -1.0 | -1.6 | -1.0 |
| | S13 BQSquare | -12.6 | -16.1 | -20.6 | -16.0 | -26.5 | -29.2 | -11.8 | -15.0 | -20.4 | -14.2 | -24.7 | -28.1 |
| | S14 BlowingBubbles | -6.0 | -6.2 | -6.8 | -6.4 | -9.4 | -11.0 | -5.4 | -5.9 | -6.7 | -5.7 | -8.3 | -9.7 |
| | S15 RaceHorsesD | -1.4 | -1.5 | -1.4 | -1.4 | -1.7 | -2.3 | -1.6 | -1.2 | -1.3 | -1.3 | -1.2 | -1.3 |
| Class E | S16 Vidyo1 | -2.4 | -2.3 | -1.8 | -2.6 | -5.4 | -3.4 | -2.5 | -2.5 | -1.3 | -2.5 | -3.4 | -2.6 |
| | S17 Vidyo3 | -6.2 | -6.3 | -6.5 | -5.0 | -4.2 | -3.8 | -6.4 | -4.7 | -6.1 | -5.5 | -3.0 | -4.1 |
| | S18 Vidyo4 | -3.0 | -2.7 | -1.9 | -2.1 | -1.3 | -0.7 | -3.5 | -1.2 | -2.7 | -2.4 | -0.7 | -0.1 |

Per sequence BD-rate (%) for all low delay settings

Conclusion

- This contribution investigates the coding efficiency improvement of low delay settings by using a different set of reference pictures as compared to HM-3.0 anchor settings.
- By using 4 reference pictures,
 - For low delay B settings,
 - **2.3%** average coding gain for high efficiency (max 7.3%),
 - **2.6%** average coding gain for low complexity (max 8.8%) .
 - For low delay P settings,
 - **2.2%** average coding gain for high efficiency (max 8.2%),
 - **2.3%** average coding gain for low complexity (max 9.1%) .
- By using 2 reference pictures,
 - For low delay B settings,
 - **3.5%** average coding gain for high efficiency (max 12.6%),
 - **3.9%** average coding gain for low complexity (max 16.0%) .
 - For low delay P settings,
 - **3.5%** average coding gain for high efficiency (max 11.8%),
 - **3.6%** average coding gain for low complexity (max 14.2%) .
- We recommend JCT-VC to consider the proposed reference pictures for low delay settings.

Question ?