

# On PCM memory usage reduction in HM software (JCTVC-G116/ M21666)


Keiichi Chono and Hirofumi Aoki  
NEC Corporation

# Summary

- Ticket57: Excessive memory allocation issue of HM software
- Removal of PCM data buffer in DPB
- Simulation results
  - No change in BD-rate results
  - Slight improvement in run time (2-3%)


# Excessive memory allocation issue of HM software (Ticket57)

- HM software decouples pixel coding and entropy coding; it keeps syntax data (needed for entropy-coding) of *every CU of every frame in DPB*.




# PCM data buffer issue

- In JCTVC reflector, it was mentioned that PCM data buffer may significantly slow down software run time.



# Removal of PCM data buffer in DPB

- Do not keep PCM data in syntax data in DPB.
- Instead, change data passes of pixel coding and entropy coding.



# Simulation

- Common test conditions (JCTVC-F900)
  - No use of PCM mode
- Computing platform
  - Windows 7 64-bit on Core7 2.8GHz and Mem. 12GB

# Simulation results (AI and RA cases)

	All Intra HE			All Intra LC		
	Y	U	V	Y	U	V
Class A	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%
Class B	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%
Class C	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%
Class D	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%
Class E	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%
Class F	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%
<b>Overall</b>	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%
	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%
Enc Time[%]	97%			96%		
Dec Time[%]	97%			98%		

	Random Access HE			Random Access LC		
	Y	U	V	Y	U	V
Class A	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%
Class B	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%
Class C	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%
Class D	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%
Class E						
Class F	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%
<b>Overall</b>	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%
	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%
Enc Time[%]	98%			98%		
Dec Time[%]	97%			97%		

# Simulation results (LB and LP cases)

	Low delay B HE			Low delay B LC		
	Y	U	V	Y	U	V
Class A						
Class B	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%
Class C	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%
Class D	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%
Class E	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%
Class F	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%
<b>Overall</b>	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%
	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%
Enc Time[%]	98%			97%		
Dec Time[%]	97%			96%		

	Low delay P HE			Low delay P LC		
	Y	U	V	Y	U	V
Class A						
Class B	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%
Class C	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%
Class D	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%
Class E	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%
Class F	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%
<b>Overall</b>	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%
	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%
Enc Time[%]	98%			98%		
Dec Time[%]	97%			97%		



# Discussions

- Removal of PCM data buffer does not change software running time significantly (on a computer with 12GB memory);
- It also does not solve the problem of Ticket 57;
- Removal of PCM data buffer from HM software seems to be a non-urgent task.

# Conclusions

- Ticket57: Excessive memory allocation issue of HM software
- Removal of PCM data buffer in DPB
- Simulation results
  - No change in BD-rate results
  - Slight improvement in run time (2-3%)
- Removal of PCM data buffer in DPB from HM software seems to be a non-urgent task

# Acknowledgement

Thanks to Panasonic for inspecting our HM-4.0 patch for PCM buffer reduction!

Empowered by Innovation

**NEC**