



Non-CE11: Parallel Context Assignment for Significance Map Coding

Tzu-Der (Peter) Chuang, Chih-Wei Hsu, Ching-Yeh Chen, Yu-Wen Huang, Shawmin Lei




Presented by Tzu-Der (Peter) Chuang
8th JCT-VC Meeting in San José
1–10 February, 2012

Overall Summary

- Method 1 – a new context formation pattern that removes dependency of three previously decoded bins for 2-level diagonal scan in large TUs
- Method 2 – a new 2-level diagonal-vertical scan with a new context formation pattern for large TUs
- Benefits of the two proposed methods
 - Allow 4-bin parallel context assignment as well
 - Unified pattern for each position in a 4x4 subblock
- Results
 - 0.2% and 0.1% bit rate increases for HE and LC, respectively
 - No run time change

Parallel Context Assignment for Sig. Map Coding


- In HM-5.0, pattern-based context formation is adopted for large TUs
- For 2-bin parallel context assignment, two patterns are used for different positions of coefficients




Extend to 3-bin or 4-bin Parallel

- Direct remove the dependency of three previously decoded
 - JCTVC-H0352 (CE11.3.1.4), JCTVC-H0253
- Non-uniform position-based context formation patterns
 - Up to 5 patterns are used, irregular mapping table


JCTVC-H0352



JCTVC-H0253




Reference types





Proposed Context Formation Pattern



- A new context formation pattern that removes dependency of three previously decoded bins
 - Designed for the 2-level diagonal scan in HM-5.0
 - Allow 4-bin parallel context assignment
 - Shift the original context formation pattern to the right by 1 pixel
 - Use the same pattern for the entire subblock



Remove the dependency of three previous bins




Proposed Pattern





4-bin Parallel

Proposed 2-level Diagonal-Vertical Scan


- To simplify the coefficient coding in subblocks, a new 2-level diagonal-vertical scan is proposed
 - Uses vertical scan within 4x4 subblocks
 - More regular and requires fewer logic gates for address generator in hardware implementation
- Use a new context formation pattern that removes dependency of the same scan line
 - Allow 4-bin parallel context assignment
 - Use the same pattern for the entire subblock



Proposed Scan




Proposed Pattern




4-bin Parallel

Results


- 0.1-0.2% bit rate increase in QP = 22, 27, 32, 37
- 0.0-0.1% bit rate increase in QP = 12, 17, 22, 27
- No run time increase



Pattern 1



Pattern 2



2-level Diag.-Ver. Scan

	AI-HE	RA-HE	LB-HE	AI-LC	RA-LC	LB-LC
2-level Diag. scan + Pattern 1	0.2	0.2	0.2	0.1	0.1	0.1
2-level Diag.-Ver. Scan + Pattern 2	0.2	0.2	0.2	0.1	0.1	0.1
2-level Diag. scan + Pattern 1 (Low QP)	0.1	0.2	0.2	0.1	0.1	0.1
2-level Diag.-Ver. Scan + Pattern 2 (Low QP)	0.2	0.2	0.2	0.1	0.1	0.1

Comparison with Other Proposals of 4-bin Parallel Context Assignment

- Our proposed methods have similar coding efficiency but with uniform pattern

Normal QP (QP = 22, 27, 32, 37)

	Pattern	AI-HE	RA-HE	LB-HE	AI-LC	RA-LC	LB-LC
JCTVC-H0253	non-uniform	0.1	0.1	0.1	0.1	0.0	0.0
JCTVC-H0352 M2	non-uniform	0.2	0.1	0.1	0.1	0.1	0.1
JCTVC-H0427 M1	non-uniform	0.1	0.1	0.1	0.1	0.1	0.1
JCTVC-H0427 M3	non-uniform	0.2	0.1	0.2	0.1	0.2	0.1
Proposed M1 (diag.-diag.)	uniform	0.2	0.2	0.2	0.1	0.1	0.1
Proposed M2 (diag.-ver.)	uniform	0.2	0.2	0.2	0.1	0.1	0.1

Low QP (QP = 12, 17, 22, 27, 32)

	Pattern	AI-HE	RA-HE	LB-HE	AI-LC	RA-LC	LB-LC
JCTVC-H0253	non-uniform						
JCTVC-H0352 M2	non-uniform	0.1	0.1	0.1	0.1	0.1	0.0
JCTVC-H0427 M1	non-uniform						
JCTVC-H0427 M3	non-uniform						
Proposed M1 (diag.-diag.)	uniform	0.1	0.1	0.1	0.0	0.1	0.0
Proposed M2 (diag.-ver.)	uniform	0.1	0.1	0.1	0.0	0.1	0.0

Conclusions

- Proposed method 1: A new context formation pattern that removes dependency of three previously decoded bins for 2-level diagonal scan
- Proposed method 2: A new 2-level diagonal-vertical scan and a new context formation pattern that removes dependency of the same scan line
- Both methods allow 4-bin parallel context assignment and use only one pattern for the entire subblock
- BD-rate=0.2% for HE, BD-rate=0.1% for LC, no run time increase