

Unification of transformed coefficient counter

Kengo Terada

Hisao Sasai

Takahiro Nishi

Panasonic Corporation

Panasonic ideas for life

Motivation

✓ Unification of transformed coefficient counters for simplification




- Draft7 : There are two counters to count the number of large level coefficients
 - Counter1 : cParam
 - For level_remaining binarization
 - Count up condition : coeff level > $3 * (1 << \text{cParam})$
 - Counter2 : numGreater1
 - For selection of ctxSet for level_greater1/2_flag context derivation
 - Count up condition : coeff level ≥ 2

Approach

✓ Removal of numGreater1

- Counter1 : cParam
 - For level_remaining binarization
 - For selection of ctxSet for level_greater1/2_flag context derivation
 - Count up condition : coeff level > $3 * (1 << \text{cParam})$

- Selection of ctxSet in Draft7







Removal of numGreater1

- Use cParam instead of numGreater1

Coefficient coding
in 16 coeff subset



Remove operations
for numGreater1

Results

BD BR luminance

	Main			HE10		
	AI	RA	LB	AI	RA	LB
Common Conditions	0.03	0.02	-0.01	0.03	0.03	-0.01
Low QP (12, 17, 22, 27)	0.01	0.00	0.00	0.01	0.01	0.01
Low QP (1, 5, 9, 13)	0.02	-0.03	0.01	-0.01	-0.03	0.02


Conclusion

It was confirmed that proposed modification can remove a counter without major impact on coding efficiency.

Recommendation

It is suggested to consider the inclusion of this proposal in the DIS of HEVC.

Draft7



Condition of “ctxSet++”


subset 3	-
subset 2	$d > 0$
subset 1	$c + (d \gg 1) > 0$
subset 0	$b + (c + (d \gg 1) \gg 1) > 0$

TU8x8

a	c
subset 0	subset 2
b	d
subset 1	subset 3

number of “level ≥ 2 ” coeff

Proposal



Condition of “ctxSet++”


subset 3	-
subset 2	$d' > 0$
subset 1	$c' > 0$
subset 0	$b' > 0$

TU8x8

a'	c'
subset 0	subset 2
b'	d'
subset 1	subset 3

number of “level > 3 ” coeff

Partial modification



Condition of “ctxSet++”

subset 3	-
subset 2	$d > 0$
subset 1	$c + (d \gg 1) > 0$
subset 0	$b + (c + (d \gg 1) \gg 1) > 0$

TU8x8

a	c
subset 0	subset 2
b	d
subset 1	subset 3

number of “level ≥ 2 ” coeff

BD BR luminance

	Proposal						Partial modification					
	Main			HE10			Main			HE10		
	AI	RA	LB	AI	RA	LB	AI	RA	LB	AI	RA	LB
Common Conditions	0.03	0.02	-0.01	0.03	0.03	-0.01						
Low QP (12, 17, 22, 27)	0.01	0.00	0.00	0.01	0.01	0.01						
Low QP (1, 5, 9, 13)	0.02	-0.03	0.01	-0.01	-0.03	0.02						