

JCTVC-L0077

Additional VUI and SEI for chroma sampling filter

Takeshi Chujoh

TOSHIBA Corporation,

Kimihiko Kazui

FUJITSU LABORATORIES LTD.

Pankaj Topiwala

FastVDO LLC.

Wei Dai

Madhu Krishnan


Marta Mrak

BBC

Andrea Gabriellini

Background 1


- In VUI, video signal specifies only chroma sample locations.
 - Consistency of chroma sampling filters is needed..




- JCTVC-K0211(FastVDO) discusses several filters which are designed to minimize loss in a single 4:2:2/4:2:0/4:2:2 (or 4:4:4/4:2:0/4:4:4) conversion.

Background 2

- A problem of chroma shift when two or more codecs are concatenated is known.



- SMPTE 2050-1:2012 defines perfect reconstruction filter set.
 - Filter coefficients for 4:2:0/4:2:2 and 4:2:2/4:2:0 conversions.



- JCTVC-L0162 and JCTVC-K0302 (BBC) discuss this case.
 - JPEG2000 5/3 filter is used.

Examples

- Degradation of repeat between down and up sampling process.




1 time




4 times



16 times



Perfect reconstruction filter



If $F_0(z) F_1(z)+F_0(z)F_1(z)=2$ then $Y_0(z) = Y_1(z)$

- **SMPTE RP 2050-1 and JPEG2000 5/3 filter are satisfied this condition.**
- **There is no degradation or repeat between down and up sampling process.**

Proposal

- A framework of VUI and SEI is introduced.
- **VUI indicates predefined chroma sampling filter set information**
 - Vertical and horizontal filter indicators
 - Vertical filtering process flag for field picture
- **Chroma sampling filtering hint SEI can specify explicit filter set information**

Proposed VUI syntax

vui_parameters() {	Descriptor
chroma_loc_info_present_flag	u(1)
if(chroma_loc_info_present_flag) {	
chroma_sample_loc_type_top_field	ue(v)
chroma_sample_loc_type_bottom_field	ue(v)
chroma_filter_info_present_flag	u(1)
if(chroma_filter_info_present_flag) {	
ver_chroma_filter_idc	u(8)
hor_chroma_filter_idc	u(8)
ver_filtering_process_flag	u(1)
}	
}	
}	

Chroma filter index in vertical direction

Value	Vertical chroma sampling filter	Informative Remark
0	Unspecified	Chroma filter is unknown or is determined by the application.
1	User-defined	Filter coefficients are specified in the chroma sampling filter hint SEI message
2	$F_V[0][0] = \{-3, -19, 34, 500, 500, 34, -19, 3\}$ $F_V[0][1] = \{19, 103, 1037, -135\}$ $F_V[1][0] = \{-8, -26, 115, 586, 409, -48, -4, 0\}$ $F_V[1][1] = \{24, -41, 1169, -128\}$ $F_V[1][2] = \{-76, 783, 330, -13\}$	SMPTE RP 2050-1:2012 Chroma sample type should be 0.
3	$F_V[0][0] = \{1, 0, -3, 0, 10, 16, 10, 0, -1, 0, 1\}$ $F_V[0][1] = \{1\}$ $F_V[0][2] = \{-1, 5, 5, -1\}$	Chroma sample type should be 2,3,4 or 5 and DistinctParityFlag should be equal to 0.
4 ... 255	Reserved	For future use by ITU-T ISO/IEC

Chroma filter index in Horizontal direction

Value	Horizontal chroma sampling filter	Informative Remark
0	Unspecified	Chroma filter is unknown or is determined by the application.
1	User-defined	Filter coefficients are specified in the chroma sampling filter hint SEI message
2	$F_H[0][0] = \{-1, 2, 6, 2, -1\}$ $F_H[0][1] = \{1\}$ $F_H[0][2] = \{1, 1\}$	ITU-T Rec. T.800 ISO/IEC15444-1, 5/3 filter
3	$F_H[0][0] = \{1, 0, -3, 0, 10, 16, 10, 0, -3, 0, 1\}$ $F_H[0][1] = \{1\}$ $F_H[0][2] = \{-1, 5, 5, -1\}$	Chroma sample type should be 0, 2 or 4.
4 ... 255	Reserved	For future use by ITU-T ISO/IEC

Proposed SEI syntax

chroma_sampling_filter_hint(payloadSize) {	Descriptor
target_format_idc	ue(v)
perfect_reconstruction_flag	u(1)
if(ver_chroma_filter_idc == 1) {	
 num_vertical_filters	ue(v)
NumVerFilters = num_vertical_filters	
if(NumVerFilters > 0)	
for(i=0; i < NumVerFilters; i++) {	
 ver_tap_length_minus1[i]	ue(v)
for(j=0; j <= ver_tap_length_minus1[i]; j++) {	
 ver_filter_coeff[i][j]	se(v)
}	
}	
}	
if(hor_chroma_filter_idc == 1) {	
 num_horizontal_filters	ue(v)
NumHorFilters = num_horizontal_filters	
if(NumHorFilters > 0)	
for(i=0; i < NumHorFilters; i++) {	
 hor_tap_length_minus1[i]	ue(v)
for(j=0; j <= hor_tap_length_minus1[i]; j++) {	
 hor_filter_coeff[i][j]	se(v)
}	
}	
}	
}	

Conclusion

- **Additional VUI and SEI message for chroma sampling filter has been proposed.**
 - Any conversion of 4:4:4, 4:2:2 and 4:2:0
- **Reduction of conversion losses of chroma format**
- **Joint four company proposal.**
 - Toshiba, Fujitsu Lab., FastVDO and BBC.

TOSHIBA
Leading Innovation >>>

FUJITSU

FastVDO

B | B | C

Example of PSNR degradation suppression

