



# **MV-HEVC/SHVC HLS: Ultra-low delay with SHVC, MV-HEVC and 3D-HEVC JCTVC-N0290/JCT3V-E0098**

Robert Skupin, Karsten Sühning, Yago Sanchez, Thomas Schierl



- Ultra-low delay (ULD) operation of base HEVC based on spatial segmentation and DU based HRD operation.
- Current HEVC extension drafts disallow ULD operation: all DUs of layer  $n$  precede all DUs of layer  $(n+1)$


Exemplary order of DUs within a 3 layer AU:



- ULD operation with HEVC extensions requires appropriate
  - NAL unit bitstream order
  - HRD operation

Control ULD mode through VPS extension flag:

**du\_interleaving\_enabled\_flag**



## Complement current extension drafts

A coded picture with `nuh_layer_id` equal to `nuhLayerIdA` shall precede in decoding order all coded pictures with `nuh_layer_id` greater than `nuhLayerIdA` in the same access unit.

with highlighted text:


If `du_interleaving_enabled_flag` is equal to 0, all VCL NAL units of a A coded picture with `nuh_layer_id` equal to `nuhLayerIdA` shall precede in decoding order the VCL NAL units of all coded pictures with `nuh_layer_id` greater than `nuhLayerIdA` in the same access unit.

Otherwise (`du_interleaving_enabled_flag` is equal to 1), all VCL NAL units of decoding unit m with `nuh_layer_id` equal to `nuhLayerIdA` shall precede in decoding order all VCL NAL units of decoding unit n with `nuh_layer_id` greater than `nuhLayerIdA` in the same access unit for which the decoding process depends on syntax elements or decoded sample values that belong to the decoding unit m.


In ULD mode:

- Decoding unit information SEI conveys DU CPB removal timings (`du_interleaving_enabled_flag` equal to 1)
- Incapable devices fall back to AU based operation.
- AU recombination with `nuh_layer_id` and NALU order as ordering constraint:
  - Single CPB: Non-consecutive memory access
  - Per-layer CPB: Consecutive layer-wise recombination

## Single CPB



## Multiple CPBs



- Current HEVC extension drafts disallow ULD operation
- **Proposed modifications:**
  - Add ULD control flag `du_interleaving_enabled_flag`
  - Adjust bitstream order of DUs in ULD mode
  - AU based HRD operation as fall back
  - AU recombination based on `nuh_layer_id` and NALU order