

Low-complexity generalized residual prediction for SHVC


JCTVC-O0107

Kwangwoon University

Image Processing Systems Laboratory


Introduction

- Inter-layer reference enhancement (based on N0204)
 - MV_{EL} is a 16x16 compressed motion vector
 - Motion compensation with SMV_{EL} may incur interpolation in both the EL and the up-sampled RL



The proposed ILR enhancement

- The inter-layer reference picture enhancement with clipped motion vector
 - Skips interpolation of both EL and the up-sampled RL by clipping SMV_{EL} to the left-top integer motion vector.
 - Weighting factor of the residual predictor (w) is set to 1



Enhanced ILRP placement

- Inter-layer reference picture (ILRP) in L0 is replaced with enhanced inter-layer reference picture (EILRP)
 - No additional reference pictures are added in the reference list



EILRP placement in the reference list

Test results on SHM3.0.1

Test conditions

Anchor	SHM3.0.1
Configuration	Random access
Spatial scalability	1.5x / 2x

The performance of the proposed ILR enhancement

Seq	BD-rate		Enc time		Dec time	
	RA 2x	RA 1.5x	RA 2x	RA 1.5x	RA 2x	RA 1.5x
Kimono	-1.3%	-0.9%	103%	88%	105%	105%
ParkScene	-0.1%	-0.3%	94%	98%	107%	105%
Cactus	-1.5%	-1.9%	94%	102%	106%	105%
BasketballDrive	-0.6%	-0.5%	94%	82%	105%	105%
BQTerrace	-0.1%	-0.2%	101%	105%	108%	107%
Average	-0.9%	-0.8%	97%	95%	106%	105%

Conclusion

- This contribution proposes a simplification of the inter-layer reference picture enhancement
- BD-rate gain of the proposed method is -0.9% and -0.8% for 1.5x and 2.0x spatial scalability, with 5% complexity increment on decoder