


M. Karczewicz, W. Pu, R. Joshi, V. Seregin

JCTVC-T0065

Non-CE1: Grouping palette indices at front



Background

- Grouping of bypass bins is beneficial for throughput
 - HEVC coefficient coding
 - HEVC intra prediction mode coding for $N \times N$
- Palette
 - Palette indices are coded in bypass mode
 - Coding of palette indices is interleaved with coding of palette run-type flag and run coding which are context coded

Proposal

- Group all the indices in the front of the block
 - Before sending `palette_run_type_flag` and run values.
- Signalling
 - Number of palette indices
 - Value of palette indices
 - last occurrence of palette run type

Signalling

- Number of indices
 - (Number of indices – indexMax) is signalled using `xWriteCoefRemainExGolomb` with `cParam = 2 + indexMax/6`
- Value of palette indices
 - No change
- Last occurrence of palette run type
 - Avoid sending the last palette run

BD-rate results for All-Intra lossy configuration

Group + 'palette share removal M1' (T0064)

	All Intra		
	G/Y	B/U	R/V
RGB, text & graphics with motion, 1080p & 720p	0.0%	0.1%	0.1%
RGB, mixed content, 1440p & 1080p	-0.1%	0.0%	0.0%
RGB, Animation, 720p	0.0%	0.0%	0.0%
RGB, camera captured, 1080p	0.0%	0.0%	0.0%
YUV, text & graphics with motion, 1080p & 720p	0.0%	0.1%	0.1%
YUV, mixed content, 1440p & 1080p	-0.2%	-0.2%	-0.1%
YUV, Animation, 720p	0.0%	0.1%	0.0%
YUV, camera captured, 1080p	0.0%	0.0%	0.0%
Enc Time[%]	111%		
Dec Time[%]	108%		

Conclusions

- Grouping of bypass bins related to index coding without loss in coding efficiency